



Triangular

Nozzle with triple edges, 3 lateral jets and 1 front jet.

This nozzle has an excellent high penetrating thrust and a very strong breaking and crushing action power on sedimented material.

Ceramic inserts are recommended using dirty or recycled water

Applications:

Cleaning of pipes and columns full of sedimented obstructions

Breaking of stones, ice, limestone, beton, concrete, small roots

Part No.	Description	Inlet	Material	Rear Jets	Front Jet	ØxL mm	Kg	Ø Pipe	Max Bar
SS Inserts									
12369.01I	Triangular Nozzle Ø 16	1/8"F	S/Steel	3 - Drilled	4 - Drilled	18x30	0,03	20 - 60	300
12370.01I	Triangular Nozzle Ø 20	1/4"F	S/Steel	3 - Drilled	4 - M4x5	20x35	0,04	25 - 80	300
12371.01/01I	Triangular Nozzle Ø 28	3/8"F	S/Steel	3 - M4x5	4 - M4x5	25x45	0,07	30 - 120	300
12372.01I	Triangular Nozzle Ø 30	1/2"F	S/Steel	3 - M6x6	4 - M6x6	30x55	0,14	40 - 100	300
12372.02I	Triangular Nozzle Ø 30	1/2"M	S/Steel	6 - M6x6	4 - M6x6	30x55	0,20	40 - 100	300
12374.01	Triangular Nozzle Ø 48	3/4"F	Steel & S/Steel	6 - M6x8	4 - M6x8	48X80	0,50	60 - 200	300
12375.01	Triangular Nozzle Ø 58	1"F	Steel & S/Steel	6 - M6x8	4 - M6x8	58x110	1,00	70 - 300	300
12376.01	Triangular Nozzle Ø 68	1" 1/4"F	Steel & S/Steel	6 - M6x8	4 - M6x8	68x125	1,00	100 - 400	300
write I (Inox) after part n for s/steel									
Ceramic Inserts									
12371.01/01C	Triangular Nozzle Ø 28	3/8"F	S/Steel	3 - M4x5	4 - M4x5	25x45	0,07	30 - 120	300
12372.01C	Triangular Nozzle Ø 30	1/2"F	S/Steel	3 - M6x6	4 - M6x6	30x55	0,14	40 - 100	300
12372.02C	Triangular Nozzle Ø 30	1/2"M	S/Steel	6 - M6x6	4 - M6x6	30x55	0,20	40 - 100	300
12374.01C	Triangular Nozzle Ø 48	3/4"F	Steel & S/Steel	6 - M6x8	4 - M6x8	48X80	0,50	60 - 200	300
12375.01C	Triangular Nozzle Ø 58	1"F	Steel & S/Steel	6 - M6x8	4 - M6x8	58x110	1,00	70 - 300	300
12376.01C	Triangular Nozzle Ø 68	1" 1/4"F	Steel & S/Steel	6 - M6x8	4 - M6x8	68x125	1,00	100 - 400	300
write I (Inox) after part n for s/steel									